

chambord

Candia

CERAMICHE

Candia
CERAMICHE

Candia Ceramiche, dopo averle selezionate, trasforma le migliori materie prime in prodotti che raccontano il valore estetico-creativo tipico del Made in Italy. Tecnologia avanzata, passione e cura fanno di ogni prodotto Candia Ceramiche un simbolo qualitativo ed estetico inimitabile.

After a thorough selection of the highest quality raw materials, Candia Ceramiche transforms them into products that faithfully reproduce the aesthetic-creative values which are emblematic of 'Made in Italy'. Cutting-edge technology, passion, and attention to detail turn every Candia Ceramiche product into an unrivalled qualitative and aesthetic symbol.

Candia
CERAMICHE

chambord

| FLOOR cement 90x90 +90x60 + 60x60 + 30x60 |



| FLOOR cement 90x90 +90x60 + 60x60 + 30x60 |



chambord









| FLOOR cement 90x90 +90x60 + 60x60 + 30x60 |




chambord




chambord

4 FORMATI / SIZES




30x60 - 12"x24" Rett.

80




60x60 - 24"x24" Rett.

80



60x90 - 24"x36" Rett.

84



90x90 - 36"x36" Rett.

88

1 SPESSORE / THICKNESS

↓
≡ 10 mm
↑

1 PEZZO SPECIALE / TRIMS



BATTISCOPA
7,5x60 - 3"x24"
Rett.


25



BATTISCOPA
8x90 - 3"x36"
Rett.

48

1 MOSAICO / MOSAICS



TRINCIATO
30x30 - 12"x12"

60

Resistenza allo scivolamento / slip resistance **R10**

3 COLORI / COLORS

sand




cement




carbon




SCHEMI DI POSA / LAYING SKETCHES




90x90 - 36"x36" **42%**
60x90 - 24"x36" **29%**
60x60 - 24"x24" **19%**
30x60 - 12"x24" **10%**




60x90 - 24"x36" **44%**
60x60 - 24"x24" **28%**
30x60 - 12"x24" **28%**




60x90 - 24"x36" **26%**
60x60 - 24"x24" **35%**
90x90 - 36"x36" **39%**



60x90 - 24"x36" **44%**
60x60 - 24"x24" **28%**
30x60 - 12"x24" **28%**



60x90 - 24"x36" **50%**
60x60 - 24"x24" **34%**
30x60 - 12"x24" **16%**



60x90 - 24"x36" **60%**
60x60 - 24"x24" **20%**
30x60 - 12"x24" **20%**

CARATTERISTICHE TECNICHE / TECHNICAL FEATURES

INFORMAZIONI TECNICHE TECHNICAL FEATURES	NORME ISO ISO NORM	VALORE PRESCRITTO DALLE NORME VALUES REQUIRED BY THE NORMS	VALORI CANDIA VALUES CANDIA
 ASSORBIMENTO ACQUA % WATER ABSORPTION %	ISO 10545-3 ASTM C-373	≤0,5%	CONFORME CONFORMING
 RESISTENZA ALLA FLESSIONE BREAKING STRENGHT	ISO 10545-4 ASTM C-648	≥35 N/mm ²	CONFORME CONFORMING
 RESISTENZA AL GELO FROST RESISTANCE	ISO 10545-12 ASTM C-1026	Richiesto Required	NON GELIVO FROST PROOF
 RESISTENZA ALL'ATTACCO CHIMICO CHEMICAL RESISTANCE	ISO 10545-13 ASTM C-650	Secondo la classificazione riportata dal fabbricante Metodo di prova disponibile GB min/min UB According to the classification statedby the manufactured Testing method available GB min/min UB	CONFORME CONFORMING
 DUREZZA MOHS MOHS HARDNESS	UNI EN 101	≥5°	6
 RESISTENZA AGLI SBALZI TERMICI THERMAL SHOCK RESISTANCE	ISO 10545-9	Metodo di prova effettuabile Test method available	RESISTENTI RESISTANT
 RESISTENZA ALL'ABRASIONE PROFONDA RESISTANCE TO DEEP ABRASION	ISO 10545-6 ASTM C-501	≤175 mm ³	CONFORME CONFORMING
 RESISTENZA ALL'ABRASIONE ABRASION RESISTANCE	ISO 10545-7	PEI	IV
 RESISTENZA ALLE MACCHIE STAIN RESISTANCE	ISO 10545-14	Classi ≥ 3	5
 COEFFICIENTE ATTRITO DINAMICO MEASUREMENT OF DINAMIC FRICTION COEFFICIENT	BOT 3000 Dynamic Coefficient of Friction D.C.O.F	> 0,40	CONFORME CONFORMING > 0,53

TABELLA IMBALLI / PACKAGING

FORMATO SIZE	SPESSORE THICKNESS	BOX			PALLET		
		PCS/BOX	MQ/BOX	KG/BOX	BOX/PALLET	MQ/PALLET	KG/PALLET
60x60 RTT	10mm	3	1,08	23,55	40	43,2	942
30x60 RTT	10mm	6	1,08	23,55	40	43,2	942
60x90 RTT	10mm	2	1,08	23,55	48	51,84	1130
90x90 RTT	10mm	2	1,62	35	20	32,4	720
MOSAICO TRANCIATO	10mm	11	0,99	21,80	36	35,64	800
7,5x60 BATTISCOPA RETT.	10mm	20	12 ML	20	40	480 ML	800

note

This image shows a blank sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

Organization & RND
ABM®

info@abmcosmos.com
www.abmcosmos.com



Ceramics of Italy